

Skip Kote Acrylic Floor Sealer

Sellador Acrílico

- Long Lasting Base Coat
- Protects Porous Floors



Technical Data Sheet

PRODUCT DESCRIPTION:

A long lasting acrylic floor sealer designed to provide a tough, durable base coat.

USES:

For use as a primer seal coat for floor finish. Can be used on resilient tile, concrete and terrazzo floors.

ADVANTAGES:

Provides an excellent base for floor finishes. Useful on older floors to seal the pores and allow floor finish to adhere properly and produce a durable bond. Permanent and not easily removed with ordinary stripping procedures to save reapplication. Water based for fast drying.

SPECIFICATIONS:

Total Solids: 16% Active Ingredients: 20% pH: 9.2-9.3 Color: Off White Solubility in Water: Mixes Odor: Acrylic Flash Point: None Viscosity: Thin Liquid Weight per Gallon: 8.45 Lbs.

PRODUCT/CONTAINER DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.



DIRECTIONS FOR PRODUCT USE:

PREPARATION OF FLOOR: Strip floor thoroughly, making sure that all old finish is removed. Rinse completely with water and allow floor to dry.

APPLICATION OF SEALER: Using a clean synthetic mop or applicator, apply an even coat of sealer and allow to dry for at least 30 minutes. A second coat may be applied. Allow to cure for 30-45 minutes then apply floor finish in the usual manner.

Coverage: 1500-2000 square feet per gallon



SSIFI

It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.

HEAI FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY

210S





MANUFACTURED BY:

 39-30 Review Avenue

 Long Island City, New York 11101

 1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366

 Division of American Wax Company, Inc.

