

# **Forever Urethane Concrete** Sealer

Sellador de Concreto Con Uretano

- Clear High Gloss Seals & Protects
- Exceptional Adhesion



## **Technical Data Sheet**

#### PRODUCT DESCRIPTION:

A heavy duty, VOC compliant, solvent based urethane system designed to seal and protect concrete floors.

For use on concrete floors as a protectant and sealer.

#### **ADVANTAGES:**

Tough wear properties, excellent adhesion. Long lasting. Prevents concrete dusting making floors easier to maintain. Superior gloss.

#### **SPECIFICATIONS:**

**Total Solids: 52%** 

pH: N/A Color: Clear

Solubility in Water: Insoluble

**Odor: Solvent** Flash Point: 145° F

**Viscosity: Heavier Than Water** Weight per Gallon: 7.9 Lbs.

#### PRODUCT/CONTAINER DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

### **SIZES AVAILABLE:**

**5 Gallon Pail** 





#### **DIRECTIONS FOR PRODUCT USE:**

PREPARATION OF FLOOR: New concrete floors should be at least 90 days old prior to application of this product. Do not apply over old, pealing seal. For optimum adhesion, floors must be abraded or etched to produce a roughened surface. Scrub floor with a degreaser to remove all grease, dirt or other foreign substance. Rinse thoroughly and allow to dry.

APPLICATION OF SEALER: Apply sealer evenly using a lamb's wool applicator or roller. Make sure extra absorbent areas receive enough seal for an even overall appearance. Do not leave a heavy surface film. Allow to dry thoroughly for about 24 hours, depending upon humidity and porosity of floor. Application of a second coat is recommended immediately after the first coat is dry to the touch.

MAINTENANCE: Sweep to remove loose soil or debris and damp mop.

NOTE: Do not buff floor surface.

Coverage: 400-600 square feet per gallon



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.









