



# Ever-Tuf 18%

## Floor Finish

Cera de Piso

- Durable • High Gloss
- Scuff Resistant



### Technical Data Sheet

#### PRODUCT DESCRIPTION:

An extremely high quality floor finish formulated with metal cross linked polymers for added resilience.

#### USES:

Can be used on any floor not affected by water including resilient tile, composition tile and terrazzo as well as varnished, painted or sealed wood and masonry flooring.

#### ADVANTAGES:

Produces a very high gloss without buffing, resists scuffs, scratches and powdering. Slip resistant, fast drying, detergent resistant, and can be spray buffed or high speed burnished.

#### SPECIFICATIONS:

- Total Solids: 18%
- pH: 9.2
- Color: Off White
- Solubility in Water: Mixes
- Odor: Acrylic
- Flash Point: None
- Viscosity: Thin Liquid
- Weight per Gallon: 8.5 Lbs.

#### PRODUCT/CONTAINER

##### DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

##### SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.



Recyclable packaging

#### DIRECTIONS FOR PRODUCT USE:

##### INITIAL APPLICATION

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse the floor thoroughly (at least twice) with clean water.
3. Repeat steps 1-2 if all old finish is not removed. Allow floor to dry.
4. Apply 3-4 thin coats using a clean synthetic mop, allowing a minimum of 30 minutes between coats.
5. Apply additional coats in same manner, allowing at least 30 minutes drying time between coats.
6. For very porous floors, an initial coat of floor sealer is recommended.

**NOTE:** Temperature, humidity and air movement affect curing time. To avoid contamination, do not return any used material to original container.

##### ROUTINE MAINTENANCE

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label instructions. For accumulated soil, lightly scrub as needed.
3. After cleaning, spray buffing or burnishing may also be done once loose dirt and dust has been swept up.
4. Additional coats may be applied if needed.


**FOR PROPER PERFORMANCE USE ONLY WHEN PRODUCT TEMPERATURE AND FLOOR TEMPERATURE ARE 50° F OR HIGHER.**

**WARNING:** Do not allow wet floor areas to be open to foot traffic. Wet shoes or wet spots can create a slippery condition. Wet floor areas should be cordoned off until dry for traffic.

Coverage: 2000-2500 square feet per gallon



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.



#### MANUFACTURED BY:



**AMERICAN** Cleaning Solutions  
Division of American Wax Company, Inc.

39-30 Review Avenue  
Long Island City, New York 11101  
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366  
Visit us on the web! [www.cleaning-solutions.com](http://www.cleaning-solutions.com)

