



Duro-Sheen

Urethane Fortified Floor Finish

Cera Con Uretano

- Super Wet-Look Gloss • Repairs Easily
- Durable • High Solids



Technical Data Sheet

PRODUCT DESCRIPTION:

A high solids, urethane enhanced floor polish formulated for use with ultra high speed floor maintenance programs.

USES:

Use in heavy traffic areas where frequent UHS burnishing is required such as supermarkets, hospitals and schools. Can be used on any floor not affected by water.

ADVANTAGES:

Produces an extremely high wet look shine that lasts due to the high polymer content and extreme durability of this urethane fortified formula. Requires little maintenance due to the resistance of dirt and black heel mark pick-up of this product. Responds to high speed burnishing for an enhanced gloss without the need of recoating.

SPECIFICATIONS:

- Total Solids: 23%
- Static Coefficient of Friction (COF) James Test Method: >0.50
- pH: 9.2
- Color: Off White
- Solubility in Water: Mixes
- Odor: Slight Acrylic
- Flash Point: None
- Viscosity: Thin Liquid
- Weight per Gallon: 8.44 Lbs.

PRODUCT/CONTAINER

DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

- 1 Gallon Bottle, 5 Gallon Pail,
- 30 & 55 Gallon Drums.



Recyclable packaging

DIRECTIONS FOR PRODUCT USE:

INITIAL APPLICATION

1. Strip existing finish from floor using a heavy duty stripper or re-emulsifier.
2. Pick-up used stripping solution with a wet vac, mop or autoscrubber.
3. Rinse the floor thoroughly (at least twice) with clean water.
4. Repeat steps 1-3 if all finish is not removed. Allow floor to dry.
5. Apply 3-4 even thin coats of finish using a clean synthetic mop, allowing 40-60 minutes drying time between coats.
6. Apply additional coats in the same manner for additional gloss, allowing at least 40-60 minutes drying time between coats.

NOTE: Temperature, humidity and air movement affect curing time. To avoid contamination, do not return any used material to original container.

ROUTINE MAINTENANCE

1. Sweep floor to remove normal traffic dirt and damp mop with a free-rinsing neutral detergent.
2. Burnish with a high speed floor machine (over 1000 RPM) using a suitable spray buffing compound or mop-on restorer to restore gloss.
3. Additional coats may be applied after thoroughly scrubbing floors.
4. Floors exposed to sand or other abrasive soils should be dry-mopped regularly with a treated dust mop prior to high speed burnishing.

FOR PROPER PERFORMANCE USE ONLY WHEN PRODUCT TEMPERATURE AND FLOOR TEMPERATURE ARE 50° F OR HIGHER.

WARNING: Do not allow wet floor areas to be open to foot traffic. Wet shoes or wet spots can create a slippery condition. Wet floor areas should be cordoned off until dry for traffic.

Coverage: 2000-2500 square feet per gallon



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY 210S



MANUFACTURED BY:



AMERICAN Cleaning Solutions
Division of American Wax Company, Inc.

39-30 Review Avenue
Long Island City, New York 11101
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366
Visit us on the web! www.cleaning-solutions.com

