



Standfast Floor Finish

Cera de Piso

- Economical • Detergent Resistant
- Durable • Non-Yellowing



Technical Data Sheet

PRODUCT DESCRIPTION:

An economical, non-yellowing and detergent resistant floor finish that combines the “repairability” of waxes with the toughness and durability of acrylic polymers.

USES:

Can be used on any floor not affected by water including resilient and composition tile and terrazzo.

ADVANTAGES:

Dries to a shine without buffing, resists scuffs and scratches, as well as powdering. It is slip resistant, fast drying, detergent resistant, does not yellow and can be restored by spray buffed using conventional rotary buffing equipment.

SPECIFICATIONS:

- Total Solids: 18%
- pH: 9.2
- Color: Off White
- Solubility in Water: Mixes
- Odor: Slight Acrylic
- Flash Point: None
- Viscosity: Thin Liquid
- Weight per Gallon: 8.45 Lbs.

PRODUCT/CONTAINER

DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

- 1 Gallon Bottle, 5 Gallon Pail,
- 30 & 55 Gallon Drums.



Recyclable packaging

DIRECTIONS FOR PRODUCT USE:

INITIAL APPLICATION

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse the floor thoroughly (at least twice) with clean water.
3. Repeat steps 1-2 if all old finish is not removed. Allow floor to dry.
4. Apply 3-4 thin coats using a clean synthetic mop, allowing a minimum of 30 minutes between coats.
5. Apply additional coats in same manner, allowing at least 30 minutes drying time between coats.
6. For very porous floors, an initial coat of floor sealer is recommended.

NOTE: Temperature, humidity and air movement affect curing time. To avoid contamination, do not return any used material to original container.

ROUTINE MAINTENANCE

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label instructions. For accumulated soil, lightly scrub as needed.
3. After cleaning, spray buffing or burnishing may also be done once loose dirt and dust has been swept up.
4. Additional coats may be applied if needed.

FOR PROPER PERFORMANCE USE ONLY WHEN PRODUCT TEMPERATURE AND FLOOR TEMPERATURE ARE 50° F OR HIGHER.

WARNING: Do not allow wet floor areas to be open to foot traffic. Wet shoes or wet spots can create a slippery condition. Wet floor areas should be cordoned off until dry for traffic.


Coverage: 2000-2500 square feet per gallon



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.



FLOOR COATING AND FINISHING MATERIAL AS TO SLIP RESISTANCE ONLY 210S



MANUFACTURED BY:



AMERICAN Cleaning Solutions
Division of American Wax Company, Inc.

39-30 Review Avenue
Long Island City, New York 11101
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366
Visit us on the web! www.cleaning-solutions.com

