



Sludge Budge

Fuel Oil Treatment

Tratamiento de Aceite Combustible

- Prevents Moisture in Fuel Oil Tanks
- Prevents Clogging • Dissolves Sludge



Technical Data Sheet

PRODUCT DESCRIPTION:

A premium blend of solvents and detergents designed to dissolve sludge and absorb moisture in fuel oil storage tanks.

USES:

As a fuel oil treatment in boiler systems.

ADVANTAGES:

Improves the combustible properties and burning efficiency of all grades of fuel oil. Aids in keeping strainers, valves, pump lines and nozzles free flowing.

SPECIFICATIONS:

Active Ingredients: 100%

pH: N/A

Color: Brown

Solubility in Water: Insoluble

Odor: Solvent

Flash Point: 150° F

Viscosity: Water Thin

Weight per Gallon: 7.8 Lbs.

PRODUCT/CONTAINER

DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.



Recyclable packaging

PRODUCT USE

DILUTION RATE

Minimal Accumulation	1 gallon per 4000 gal. of fuel oil
Heavy Accumulation	1 gallon per 1000-2500 gallons of fuel oil

DIRECTIONS FOR PRODUCT USE:

1. Add directly to fuel oil storage tank, preferably prior to oil delivery providing a natural mixing.
2. Agitation will facilitate the dispersion throughout the oil if added to a full or partial tank.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.

Refer to SDS for further safety information.



MANUFACTURED BY:



AMERICAN Cleaning Solutions
Division of American Wax Company, Inc.

39-30 Review Avenue
Long Island City, New York 11101
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366
Visit us on the web! www.cleaning-solutions.com

