

Econo

Sludge Budge **Fuel Oil Treatment**

Tratamiento de Aceite Combustible

- Prevents Moisture in Fuel Oil Tanks
- Prevents Clogging
 Dissolves Sludge



Technical Data Sheet

PRODUCT DESCRIPTION:

An economical blend of solvents and detergents designed to dissolve sludge and absorb moisture in fuel oil storage tanks.

As a fuel oil treatment in boiler systems.

ADVANTAGES:

Improves the combustible properties and burning efficiency of all grades of fuel oil. Aids in keeping strainers, valves, pump lines and nozzles free flowing.

SPECIFICATIONS:

Active Ingredients: 100%

pH: N/A Color: Brown

Solubility in Water: Insoluble

Odor: Solvent Flash Point: 150° F **Viscosity: Water Thin** Weight per Gallon: 7.8 Lbs.

PRODUCT/CONTAINER **DISPOSAL:**

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.





PRODUCT USE

DILUTION RATE

| | Minimal Accumulation | 1 gallon per 4000 gal. of fuel oil |
|--|----------------------|--|
| | Heavy Accumulation | 1 gallon per 1000-2500 gallons of fuel oil |

DIRECTIONS FOR PRODUCT USE:

- 1. Add directly to fuel oil storage tank, preferably prior to oil delivery providing a natural mixing.
- 2. Agitation will facilitate the dispersion throughout the oil if added to a full or partial tank.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.

Refer to SDS for further safety information.







