



Super Strip

Ammoniated Stripper

Estripádo Con Amoníaco

- Powerful • Concentrated
- Heavy Duty



Technical Data Sheet

PRODUCT DESCRIPTION:

A powerful formulation that combines detergents, alkali salts, butyl and ammonia to strip even the toughest build-ups.

USES:

Strips off wax & finish with the use of an automatic floor machine or a standard rotary machine equipped with a stripping pad.

ADVANTAGES:

Powerful fast acting, ammoniated formula, designed for general removal of wax and finish from resilient floor tiles. Formulated with low sudsing properties that are well suited for use in automatic floor machines as well as simple mop stripping. Effective in both hard and soft water.

SPECIFICATIONS:

Active Ingredients: 20%
 pH: 13
 Color: Fluorescent Yellow
 Solubility in Water: Complete
 Odor: Ammonia
 Flash Point: None
 Viscosity: Water Thin
 Weight per Gallon: 8.85 Lbs.

PRODUCT/CONTAINER

DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.



Recyclable packaging

PRODUCT USE

DILUTION RATE

Light Build-Up	12 oz. per gallon of hot water
Moderate Build-Up	32 oz. per gallon of hot water
Heavy Build-Up	64 oz. per gallon of hot water

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE
PRODUCT DESIGNED FOR USE WITH HOT WATER

DIRECTIONS FOR PRODUCT USE:

FOR BEST RESULTS, USE OF FLOOR MACHINE RECOMMENDED

1. Dilute concentrate per the chart above based on the amount of build-up.
2. Make sure room is well ventilated! Apply to a small test area to determine the amount of time needed to adequately strip floor.
3. Mop diluted solution liberally onto floor surface working in 5' x 5' sections.
4. Allow to stand 4-5 minutes. Keep area wet and well ventilated.
5. If surface is unusually dirty or scuffed, use mop, brush or floor machine to agitate and loosen dirt and finish; for stubborn marks scrub using a stripping pad.
6. Pick up solution with a mop or wet-vac machine. No rinsing required if a wet-vac is used.
7. Allow floor to dry.
8. Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

CAUTION: Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.



MANUFACTURED BY:



AMERICAN Cleaning Solutions
 Division of American Wax Company, Inc.

39-30 Review Avenue
 Long Island City, New York 11101
 1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366
 Visit us on the web! www.cleaning-solutions.com

