

# FS 22

## Floor Stripper

Piso Estripado

- Biodegradable
- Environmentally Responsible Ingredients



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.



## Technical Data & Training Sheet

### PRODUCT DESCRIPTION:

A highly effective, fast acting, non-corrosive, low odor, floor finish and wax remover. This product will strip **FOCUS ZF 33 Zinc-Free Floor Finish** as well as other green floor finishes.

### USES:

Easy and fast removal of multiple coats of floor finish, wax or acrylic seal with or without the use of a conventional floor machine and stripping pad.

### ADVANTAGES:

**GREEN SEAL™ CERTIFIED** under GS-40 standard for industrial and institutional floor-care products. Environmentally responsible formula does not contain 2-butoxyethanol, ammonia, nonylphenol surfactants, dye or fragrance.

### SPECIFICATIONS:

pH: 11  
Color: Clear, colorless.  
Solubility in Water: Complete  
Odor: Mild, No fragrance added  
Flash Point: N/A  
Viscosity: Water thin liquid  
Weight per Gallon: 8.5 Lbs.

### PRODUCT/CONTAINER

#### DISPOSAL:

Dispose of used/unused/unwanted product according to Federal, state & local regulations. Offer container for recycling.

### SIZES AVAILABLE:

1 Gallon, 5 Gallons, 30 & 55 Gallons.



Recyclable packaging

### DIRECTIONS FOR PRODUCT USE:

PURPOSE	DILUTIONS
<b>LIGHT BUILD-UP</b>	1:8 (16 oz. concentrate per gallon of cold water) 1:8 (16 onzas concentrado cada galón de agua fría)
<b>MODERATE BUILD-UP</b>	1:4 (32 oz. concentrate per gallon of cold water) 1:4 (32 onzas concentrado cada galón de agua fría)
<b>HEAVY BUILD-UP</b>	1:2 (64 oz. concentrate per gallon of cold water) 1:2 (64 onzas concentrado cada galón de agua fría)

**NOTE:** Improper dilution may result in damage to surfaces and may increase the risk of health effects.



Stripper should be diluted with cold water!



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Respiratory protection is generally not required. No special ventilation is normally required. Refer to SDS for further safety information.



1. Apply a liberal amount of solution to the floor and let penetrate for 3 to 5 minutes.



2. Work in small enough areas so as not to allow stripper to dry. Use another wet mop to pick up the re-emulsified floor finish.



3. For heavy build-up a floor machine may be necessary.



4. Rinse floor with clean water and allow to dry thoroughly.



5. Apply 3-4 coats of **ZF 33 Zinc-Free Seal & Finish** with mop or applicator to produce a long lasting and durable shine.

### MANUFACTURED BY:

39-30 Review Avenue  
Long Island City, New York 11101  
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366  
Visit us on the web! [www.focus-ac.com](http://www.focus-ac.com)

