



# Laser Rinseless Mop Strip

Estripádo Sin Enjuague

- Instant Emulsification • Penetrating
- Time Saver • Works With Cold Water



## Technical Data Sheet

### PRODUCT DESCRIPTION:

A non-corrosive, rinseless, mop-on stripper formulated to immediately rip off multiple layers of finish or sealer using cold or warm water.

### USES:

Strips off multiple coats of wax and finish without the use of a floor machine and stripping pad.

### ADVANTAGES:

Cuts through many layers of sealer and finish in minutes. No rinse is necessary when the residue is picked up with a wet vacuum. A tremendous time and labor saver. Non-corrosive.

### SPECIFICATIONS:

Active Ingredients: 70%

pH: 12

Color: Blue

Solubility in Water: Complete

Odor: Lemon

Flash Point: None

Viscosity: Water Thin

Weight per Gallon: 8.1 Lbs.

### PRODUCT/CONTAINER

#### DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

### SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.



Formula #9156L



### PRODUCT USE

### DILUTION RATE

Light Build-Up	8 oz. per gallon of cold or warm water
Medium Build-Up	32 oz. per gallon of cold or warm water
Heavy Build-Up	64 oz. per gallon of cold or warm water

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE  
PRODUCT DESIGNED FOR USE WITH WARM WATER

### DIRECTIONS FOR PRODUCT USE:

FOR BEST RESULTS, USE OF WET-VAC IS RECOMMENDED

1. Dilute concentrate per the chart above based on the amount of build-up.
2. Apply to a small test area to determine the amount of time needed to adequately strip floor.
3. Mop diluted solution liberally onto floor surface working in 5' x 5' sections or use autoscrubber for application.
4. Allow to stand 4-5 minutes. Keep area wet.
5. If surface is unusually dirty or scuffed, use mop, brush or floor machine to agitate and loosen dirt and finish; for stubborn marks scrub using a stripping pad.
6. Pick up solution with a mop or wet-vac machine. No rinsing required if a wet-vac is used.
7. Allow floor to dry.
8. Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

**CAUTION:** Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.



### MANUFACTURED BY:



39-30 Review Avenue  
Long Island City, New York 11101  
1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366  
Visit us on the web! [www.cleaning-solutions.com](http://www.cleaning-solutions.com)

