



Photon

Low Odor Rinse Free Stripper

Estripádo de Olor Minimal Sin Enjuague

- Instant Emulsification • Rapid Penetration
- Time Saver • Works With Cold Water



Technical Data Sheet

PRODUCT DESCRIPTION:

Our most effective, quickest acting floor stripper. It has been formulated with special odor-suppressing ingredients, making it a great choice for sensitive environments where odor is an issue. Its non-alkaline composition makes it truly a no-rinse product.

USES:

Strips off multiple coats of wax and finish. Ideal for use in schools, hospitals, office buildings etc.

ADVANTAGES:

Cuts through many layers of sealer and finish in minutes. No rinse is necessary when the residue is picked up with a wet vacuum. A tremendous time and labor saver. Non-corrosive, low foaming.

SPECIFICATIONS:

Active Ingredients: 45-50%
 pH: 11
 Color: Clear
 Solubility in Water: Complete
 Odor: Mild, Butyl
 Flash Point: None
 Viscosity: Water Thin
 Weight per Gallon: 8.26 Lbs.

PRODUCT/CONTAINER

DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.



Recyclable packaging

PRODUCT USE

DILUTION RATE

Light Build-Up	8 oz. per gallon of cold water
Medium Build-Up	32 oz. per gallon of cold water
Heavy Build-Up	64 oz. per gallon of cold water

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE
PRODUCT DESIGNED FOR USE WITH COLD WATER

DIRECTIONS FOR PRODUCT USE:

FOR BEST RESULTS, USE OF WET-VAC IS RECOMMENDED

1. Dilute concentrate per the chart above based on the amount of build-up.
2. Apply to a small test area to determine the amount of time needed to adequately strip floor.
3. Mop diluted solution liberally onto floor surface working in 5' x 5' sections or use autoscrubber for application.
4. Allow to stand 4-5 minutes. Keep area wet.
5. If surface is unusually dirty or scuffed, use mop, brush or floor machine to agitate and loosen dirt and finish; for stubborn marks scrub using a stripping pad.
6. Pick up solution with a mop or wet-vac machine. No rinsing required if a wet-vac is used.
7. Allow floor to dry.
8. Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

CAUTION: Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.

Refer to SDS for further safety information.



MANUFACTURED BY:

39-30 Review Avenue
 Long Island City, New York 11101
 1-888 WAX PLUS • (718) 392-8080 Fax: (718) 482-9366
 Visit us on the web! www.cleaning-solutions.com

