


Super Citrus Solv

Emulsifying Cleaner/Degreaser

Limpiador/Desengrasante Emulsionante

- Cleans
 Degreases
 Super Concentrate
- Deodorizes



Technical Data Sheet

PRODUCT DESCRIPTION:

An economic, highly concentrated, natural citrus based cleaner, degreaser and deodorizer. Formulated with pure d-limonene combines with emulsifiers.

USES:

Effective for many cleaning tasks including the removal of mastic, glue, gum, tar and grease. Excellent for use on sump & grease traps, floors, walls, parts washing, etc.

ADVANTAGES:

A natural citrus extract, highly concentrated and extremely powerful. An excellent grease & oil solvent, non-corrosive, which cleans without petroleum solvent odors. Contains no caustics or no acids. Leaves a pleasant citrus odor. Environmentally friendly.

SPECIFICATIONS:

Active Ingredients: 100%

pH: N/A

Color: Light Yellow

Solubility in Water: Forms Emulsion

Odor: Citrus Flash Point: 150° F Viscosity: Slight

Weight per Gallon: 6.7 Lbs.

PRODUCT/CONTAINER DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail. 30 & 55 Gallon Drums.



	Recyclable
	Recyclable packaging
- 4	

PRODUCT USE

DILUTION RATE

Grease Traps	1oz. per qt. of water for every 20 gal. trap capacity
Drains and Drain Lines	4 oz. per qt. of water

DILUTION MAY VARY DEPENDING UPON SEVERITY OF SOIL BUILD-UP

DIRECTIONS FOR PRODUCT USE:

Product should be applied in the evening when the system is inactive. Once diluted solution has been applied, allow to stand at least 2 hours or preferably overnight for best results.

GREASE TRAPS:

- 1. Thoroughly clean trap of accumulated grease.
- 2. Pour into trap each evening a solution of 1 oz. concentrate & 1 qt. of water for every 20 gal. of trap capacity.
- 3. Regular application will continue to keep trap grease and odor free.

NOTE: Application may be increased or decreased based on the amount of grease entering the trap.

DRAIN & DRAIN LINES:

- 1. To clean grease deposits, pour down drain a solution of 4 oz. concentrate and 1 quart of water.
- 2. Depending upon grease build-up, repeated application may be required.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.









