


Citrus Grease Solv

Multi-Purpose Cleaner/Degreaser

Limpiador/Desengrasante Multiuso

- Cleans
 Degreases
 Super Concentrate
- Deodorizes



Technical Data Sheet

PRODUCT DESCRIPTION:

A highly concentrated, natural citrus based cleaner, degreaser and deodorizer. Formulated with pure dlimonene combined with emulsifiers.

USES:

Multi-purpose cleaning/degreasing of a wide variety of surfaces including sump and grease traps, drain lines, floors, walls, parts washing etc. Especially effective for the removal of mastic, glue, gum, tar and grease.

ADVANTAGES:

Highly concentrated and extremely powerful. A noncorrosive grease & oil solvent, that cleans without petroleum solvent odors. Contains no caustics or no acids. Leaves a pleasant citrus odor. Environmentally friendly. Safe to use in drain lines & septic systems.

SPECIFICATIONS:

Active Ingredients: 100%

pH: N/A

Color: Light Yellow

Solubility in Water: Complete

Odor: Citrus Flash Point: 150° F Viscosity: Slight

Weight per Gallon: 7.5 Lbs.

PRODUCT/CONTAINER **DISPOSAL:**

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.





Recyclable packaging

PRODUCT USE

DILUTION RATE

Remove Tar, Asphalt, Tire Marks, Rug/Upholstery Stains, Soap Scum, HD Degreasing Engines/Motors	Full strength
Chemical Toilets	3 oz. per 30 gal. capacity
Deodorizing	4 oz. per gallon of water
General Purpose Cleaning/Degreasing	5-6 oz. per gallon of water
Grease Traps & Drain Lines	8-10 oz. per gallon of water
Sewage Plants, Septic Tanks, Drain Fields	1 qt. per 1000 gal. capacity

DO NOT EXCEED RECOMMENDED DOSAGE LISTED ABOVE!

DIRECTIONS FOR PRODUCT USE:

DO NOT USE ON PLASTIC OR PAINTED SURFACES

- 1. Follow dilution instructions above for appropriate task.
- 2. For hard sufaces, apply solution by spraying or wiping, allow to penetrate for 1-5 minutes depending upon soil level; scrub if needed.
- 3. Rinse surface thoroughly with clean water. Engine or motor parts may be rinsed using pressure spray or steam.
- 4. For stain removal, apply to stain, allow to penetrate then blot area with a clean cloth adding a small amount of water and blot again until stain disappears.
- 5. Pour into drain or trap or dispense using a drip device.



MANUFACTURED BY:

It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to SDS for further safety information.







