

# Bounce

## Synthetic Gym Floor Finish

Cera Sintética Para Pisos de Gimnasio

- Water-Based Protects Rubber Floors
- Durable Scuff Resistant



## **Technical Data Sheet**

#### PRODUCT DESCRIPTION:

A water-based, acrylic urethane sealer/finish specifically formulated for synthetic gym and athletic floors.

For use on synthetic gym and althletic floors as a sealer, permanent finish and protectorant.

#### **ADVANTAGES:**

Tough wear properties. Excellent adhesion. Long lasting. Povides a flexible protective coating with outstanding durability and scuff resistance.

#### **SPECIFICATIONS:**

Total Solids: 20%

pH: 9

Color: Opaque, Off White Solubility in Water: Complete

**Odor: Acrylic** Flash Point: N/A

**Viscosity: Heavier Than Water** Weight per Gallon: 7.45 Lbs.

### PRODUCT/CONTAINER **DISPOSAL:**

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

#### **SIZES AVAILABLE:**

5 Gallon Pail





#### **DIRECTIONS FOR PRODUCT USE:**

PREPARATION OF FLOOR: Strip floor thoroughly, making sure that all old finish is removed. completely with water and allow to dry.

APPLICATION OF SEALER: Using a clean synthetic mop or applicator, apply a thin even coat and allow to dry for 30 minutes. For higher gloss and maximum durability a second coat should be applied, allowing 30 minutes of drying time between coats depending upon temperature and humidity.

MAINTENANCE: Sweep floors daily to remove all excessive soil, dirt and grit with a clean, treated dust mop. Damp mop as necessary with a neutral cleaner. This will not damage or dull gloss. Apply an additional coat when necessary.

Coverage: 1500-2000 square feet per gallon



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products. Refer to MSDS for further safety information.







