

Prime Zyme

Enzyme Digestant Deodorant Cleaner

Desodorisante y Limpiador Con Enzimas

- Eliminates Organic Waste
 Cleans and Deodorizes
- Maintains Drain Lines



Technical Data Sheet

PRODUCT DESCRIPTION:

A bacterial enzyme-based formulation that is designed to digest and eliminate organic stains, soils and odors. A "natural" solution for cleaning and maintaining drain lines.

Cleans and maintains drain lines and controls malodors commonly found in bathrooms, kitchens, garbage collection areas, kennels, etc

ADVANTAGES:

All natural, solvent-free, non-flammable, non-corrosive and fast acting. The enzyme producing non-pathogenic bacteria in this formulation actually digest the proteins that produce odors, stains and grease clogs.

SPECIFICATIONS:

Active Ingredients: 25%

pH: 6-7

Color: Cloudy White

Solubility in Water: Complete

Odor: Spring Mint Flash Point: None **Viscosity: Water Thin** Weight per Gallon: 8.5 Lbs.

PRODUCT/CONTAINER **DISPOSAL:**

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Quart Bottle, 1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.





PRODUCT USE

DILUTION RATE

Surface Odor Contol	Full strength on surface
Carpet Odor & Stain Removal	Full strength on soiled area
Grease Traps	Initial: 16 oz. per 20 cu. ft. capacity Maintenance: 16 oz. weekly to trap
Clog Prevention	4 oz. per 2 inch of inside pipe diameter
Septic Tanks	Initial: 64 oz. directly into tank thru manhole Maintenance: 8 oz. weekly into toilet

DIRECTIONS FOR PRODUCT USE:

DO NOT USE WITH HOT WATER, BLEACH, DISINFECTANT OR CHEMICAL DRAIN OPENERS. THIS WILL REDUCE PRODUCT PERFORMANCE.

ODOR CONTROL: Do not spray into air or use as an air freshener. Apply with a trigger sprayer, sponge, mop or cloth. Product must contact surface to be effective.

CARPET ODOR & STAIN REMOVER: Remove solid waste. Test in an inconspicuous area for colorfastness before applying product. Apply liberally to soiled area, brush and rub in well. Let stand 20-30 minutes. Rinse with water and blot up or extract.

GREASE TRAPS: Initial Application - Pour 16 oz. in trap for every 20 cu. ft. of capacity. Follow with 8 oz. of warm water for each pint used. Maintenance - Add 16 oz. of product to grease trap weekly.

CLOG PREVENTION: Use 4 oz. for every 2 inch of inside pipe diameter 2-4 times a week. For best results, treat at the end of the day when flow

SEPTIC TANKS: Pour 64 oz. directly into tank through the manhole cover. Maintenance - Initially add 16 oz. per 25 cu.ft. of capacity. Weekly pour 8 oz. directly into toilet and flush.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.

Refer to SDS for further safety FIRE HAZARD information. **HEALTH HAZARD** REACTIVITY SPECIFIC HAZARD







