

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 8/7/2018 Supersedes: 10/27/2025

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Product name : Soap Film Remover

Product code : 155-4515

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet

cleaners, metal cleaners)

1.4. Supplier's details

American Cleaning Solutions 39-30 Review Avenue Long Island City, NY, 11101 T (718) 392-8080

1.5. Emergency phone number

Emergency number : INFOTRAC: 800-535-5053

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral), Category 4 H302 Harmful if swallowed.

Skin corrosion/irritation, Category 1 H314 Causes severe skin burns and eye damage.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dusts or mists.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing

protection.

P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a poison center/doctor

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P363 - Take off immediately all contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Potassium Hydroxide, 45%≤conc<50%, aqueous solutions	CAS-No.: 1310-58-3	10 – 20	Acute Tox. 3 (Oral), H301 Skin Corr. 1, H314
Nonylphenol Ethoxylate	CAS-No.: 127087-87-0	1 – 5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
butyl glycolether	CAS-No.: 111-76-2	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
tetrasodium ethylene diamine tetracetate	CAS-No.: 64-02-8	1 – 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

8/7/2018 (Issue date) EN (English US) 2/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel

unwell. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met. Harmful if swallowed.

Symptoms/effects

: Causes severe skin burns and eve damage.

Symptoms/effects after ingestion

: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Ventilate area. **Emergency procedures**

Environmental precautions Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public

waters.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

See Heading 8. Exposure controls and personal protection.

8/7/2018 (Issue date) EN (English US) 3/13

Safety Data Sheet

Hygiene measures

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of

Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after

vapor. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

handling.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces,

sparks, open flame and other ignition sources. No smoking. Keep container closed when not in

use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>		
USA - ACGIH - Occupational Exposure Limits		
Local name	Potassium hydroxide	
Remark (ACGIH)	URT, eye, & skin irr	
butyl glycolether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH OEL TWA	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)	
Remark (ACGIH)	Eye & URT irr	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL TWA	240 mg/m³	
	50 ppm	

8.2. Appropiate engineering controls

No additional information available

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand	protection:
nanu	protection:

Wear protective gloves/eye protection/face protection protective gloves

Eye protection:

Chemical goggles or face shield

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):





Other information:

Do not eat, drink or smoke during use.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Color : light brown
Odor : mild

Odor threshold : No data available

pH : 14

Melting point: No data availableFreezing point: No data availableBoiling point: $212 - 220 \,^{\circ}F$ Flash point: ≥ $200 \,^{\circ}F$ Flammability (solid, gas): Non flammable.Vapor pressure: No data availableRelative vapor density at 20 $\,^{\circ}C$: Same as water

Relative density : 1.03

Solubility : Soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Explosion limits : No data available

Particle characteristics : No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : corrosive vapors.

SECTION 11 Toxicological information

11.1. Likely rou	tes of exposure
------------------	-----------------

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Soap Film Remover		
ATE US (oral)	1597.611 mg/kg body weight	
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,>		
LD50 oral rat	273 mg/kg (Rat, Oral)	
ATE US (oral)	273 mg/kg body weight	
butyl glycolether (111-76-2)		
I DEC. 1	0000 # 1 1 1 1 1 1 1 0 0 0 0 0 0 0 0 0 0	

butyl glycolether (111-76-2)	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 Inhalation - Rat	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 Inhalation - Rat [ppm]	450 – 486 ppm/4h 450-486,Rat
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	435 mg/kg body weight
ATE US (gases)	450 ppmV/4h
ATE US (vapors)	2.17 mg/l/4h
ATE US (dust, mist)	2.17 mg/l/4h

Nonylphenol Ethoxylate (127087-87-0)		
LD50 oral rat	1890 mg/kg body weight (Rat, Male / female, Experimental value, Oral)	
LD50 oral	657 mg/kg body weight (Rabbit, Male / female, Experimental value, Oral)	
ATE US (oral)	1890 mg/kg body weight	
tetrasodium ethylene diamine tetracetate (64-02-8)		
LD50 oral rat	1780 – 2000 mg/kg (Rat, Male / female, Experimental value, Oral)	
ATE US (oral)	1780 ma/ka body weight	

Skin corrosion/irritation : Causes severe skin burns.

pH: 14

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

oH .	14 (5 %)	
Nonylphenol Ethoxylate (127087-87	.0)	
рН	6.3 (1 %)	
tetrasodium ethylene diamine tetracetate (64-02-8)		
рН	11 (1 %)	
Serious eye damage/irritation	: Assumed to cause serious eye damage pH: 14	
Potassium Hydroxide, 45%= <conc<< td=""><td>50%, aqueous solutions (1310-58-3)</td></conc<<>	50%, aqueous solutions (1310-58-3)	
рН	14 (5 %)	
Nonylphenol Ethoxylate (127087-87	.0)	
рН	6.3 (1 %)	
tetrasodium ethylene diamine tetrac	etate (64-02-8)	
рН	11 (1 %)	
Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity	Not classified Not classified Not classified	
butyl glycolether (111-76-2)		
IARC group	3 - Not classifiable	
Reproductive toxicity STOT-single exposure STOT-repeated exposure Aspiration hazard	Not classified Not classified Not classified Not classified Not classified	
Potassium Hydroxide, 45%= <conc<< td=""><td>50%, aqueous solutions (1310-58-3)</td></conc<<>	50%, aqueous solutions (1310-58-3)	
Viscosity, kinematic	5.705 mm ² /s	
butyl glycolether (111-76-2)	<u>'</u>	
Viscosity, kinematic	3.659 mm ² /s	
tetrasodium ethylene diamine tetrac	vetate (64-02-8)	
Viscosity, kinematic	Not applicable (solid)	
Potential Adverse human health effects and symptoms Symptoms/effects Symptoms/effects after ingestion	 : Based on available data, the classification criteria are not met. Harmful if swallowed. : Causes severe skin burns and eye damage. : Swallowing a small quantity of this material will result in serious health hazard. 	

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3)

LC50 - Fish [1] 80 mg/l (96 h, Gambusia affinis, Pure substance)

8/7/2018 (Issue date) EN (English US) 7/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nonylphenol Ethoxylate (127087-87-0)		
LC50 - Fish [1]	11.6 mg/l (48 h, Oryzias latipes, Static system, Fresh water, Experimental value)	
EC50 - Crustacea [1]	14 mg/l (48 h, Daphnia magna, Static renewal, Fresh water, Experimental value)	
EC50 96h - Algae [1]	12 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)	
tetrasodium ethylene diamine tetracetate (64-02-8)		
LC50 - Fish [1]	121 mg/l (US EPA, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Soft water)	
EC50 - Crustacea [1]	625 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)	
LC50 - Fish [2]	396 mg/l	
ErC50 algae	> 100 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Weight of evidence, Nominal concentration)	

12.2. Persistence and degradability

Soap Film Remover		
Persistence and degradability	Not established.	
Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" td=""></conc<50%,>		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water, Biodegradable in the soil, Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance	
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance	
ThOD	2.305 g O₂/g substance	
BOD (% of ThOD)	0.31	
Nonylphenol Ethoxylate (127087-87-0)		
Persistence and degradability	Not readily biodegradable in water, Biodegradable in water.	
tetrasodium ethylene diamine tetracetate (64-02-8)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance	
Chemical oxygen demand (COD)	0.54 – 0.58 g O₂/g substance	

12.3. Bioaccumulative potential

Soap Film Remover	
Bioaccumulative potential	Not established.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>		
Bioaccumulative potential	Not bioaccumulative.	
butyl glycolether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Nonylphenol Ethoxylate (127087-87-0)		
BCF - Fish [1]	7.6 – 12.4 l/kg (6 week(s), Cyprinus carpio, Static system, Fresh water, Experimental value)	
Partition coefficient n-octanol/water (Log Pow)	5.67 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Low potential for bioaccumulation (molecular mass >=700 g/mol).	
tetrasodium ethylene diamine tetracetate (64-02-8)		
BCF - Fish [1]	1.1 – 1.8 (28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	-13.17 (Estimated value, KOWWIN)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

Potassium Hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>				
Ecology - soil	No (test)data on mobility of the component(s) available.			
butyl glycolether (111-76-2)				
Surface tension	0.027 N/m (25 °C)			
Nonylphenol Ethoxylate (127087-87-0)				
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.631 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)			
Ecology - soil	No (test)data on mobility of the substance available. Low potential for adsorption in soil.			
tetrasodium ethylene diamine tetracetate (64-02-8)				
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.495 (log Koc, SRC PCKOCWIN v2.0, Calculated value)			
Ecology - soil	Low potential for adsorption in soil.			

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

Other information : Avoid release to the environment.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Ecological information : Avoid release to the environment.

8/7/2018 (Issue date) EN (English US) 9/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14 Transport information

14.1. UN number

UN-No. (DOT) : NA1760
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Compounds, cleaning liquid

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No.(DOT) : NA1760

8/7/2018 (Issue date) EN (English US) 10/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

: 30 L

TDG

No data available

IMDG

No data available

IAT/

No data available

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Potassium Hydroxide, 45%≤conc<50%, aqueous solutions	1310-58-3	Present	Active	
butyl glycolether	111-76-2	Present	Active	
Nonylphenol Ethoxylate	127087-87-0	Present	Active	XU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	CAS-No.	Listing	Commercial status	Flags
tetrasodium ethylene diamine tetracetate	64-02-8	Present	Active	

Potassium Hydroxide, 45%=<conc<50%, aqueous solutions (1310-58-3) Not subject to reporting requirements of the United States SARA Section 313 CERCLA RQ 1000 lb

15.2. International regulations

CANADA

Nonylphenol Ethoxylate (127087-87-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. State regulations

No additional information available

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date : 8/7/2018
Other information : None.

Full text of hazard classes and H-statements	
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B - Safety glasses, Gloves

8/7/2018 (Issue date) EN (English US) 12/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.