

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/16/2019 Supersedes: 9/25/2025

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Product name : Power Foam Degreaser

Product code : 155-8599

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Degreaser.

1.4. Supplier's details

American Cleaning Solutions 39-30 Review Avenue Long Island City, NY, 11101 T (718) 392-8080

1.5. Emergency phone number

Emergency number : INFOTRAC: 800-535-5053

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1 H314 Causes severe skin burns and eye damage.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dusts or mists.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing

protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor

P321 - Specific treatment (see supplemental first aid instruction on this label).
P363 - Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
butyl glycolether	CAS-No.: 111-76-2	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Sodium dodecylbenzenesulfonate	CAS-No.: 25155-30-0	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Irrit. 2, H315 Eye Dam. 1, H318
Nonylphenol Ethoxylate	CAS-No.: 127087-87-0	1 – 5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

4.1. Description of necessary first-aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician. If eye irritation persists: Get medical advice/attention.

: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

5/16/2019 (Issue date) EN (English US) 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public

waters.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

See Heading 8. Exposure controls and personal protection.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of

vapor. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Wash hands and forearms thoroughly after handling.

5/16/2019 (Issue date) EN (English US) 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces,

sparks, open flame and other ignition sources. No smoking. Keep container closed when not in

use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

butyl glycolether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH OEL TWA	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)	
Remark (ACGIH)	Eye & URT irr	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL TWA	240 mg/m³	
	50 ppm	

8.2. Appropiate engineering controls

No additional information available

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves/eye protection/face protection protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):





Other information:

Do not eat, drink or smoke during use.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Color : clear
Odor : mild

Odor threshold : No data available

pH : 13

 Melting point
 : No data available

 Freezing point
 : No data available

 Boiling point
 : 212 − 220 °F

 Flash point
 : ≥ 200 °F

 Flammability (solid, gas)
 : Non flammable.

 Vapor pressure
 : No data available

Relative vapor density at 20 $^{\circ}$ C : 1 (\geq 1) Relative density : 1.046

Solubility : Soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Explosion limits : No data available

Particle characteristics : No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : corrosive vapors.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified

5/16/2019 (Issue date) EN (English US) 5/12

Safety Data Sheet

Carcinogenicity

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (definal) Acute toxicity (inhalation)	: Not classified			
butyl glycolether (111-76-2)	. Not diagramed			
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)			
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)			
LC50 Inhalation - Rat	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)			
LC50 Inhalation - Rat [ppm]	450 – 486 ppm/4h 450-486,Rat			
ATE US (oral)	500 mg/kg body weight			
ATE US (dermal)	435 mg/kg body weight			
ATE US (gases)	450 ppmV/4h			
ATE US (vapors)	2.17 mg/l/4h			
ATE US (dust, mist)	2.17 mg/l/4h			
Nonylphenol Ethoxylate (127087-87-0)				
LD50 oral rat	1890 mg/kg body weight (Rat, Male / female, Experimental value, Oral)			
LD50 oral	657 mg/kg body weight (Rabbit, Male / female, Experimental value, Oral)			
ATE US (oral)	1890 mg/kg body weight			
Sodium dodecylbenzenesulfonate (25155-30-0)				
LD50 oral rat	1080 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))			
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))			
LC50 Inhalation - Rat	0.31 mg/l (4 h, Rat, Male, Experimental value, Inhalation (aerosol), 14 day(s))			
ATE US (oral)	1080 mg/kg body weight			
ATE US (vapors)	0.31 mg/l/4h			
ATE US (dust, mist)	0.31 mg/l/4h			
Skin corrosion/irritation	: Causes severe skin burns. pH: 13			
Nonylphenol Ethoxylate (127087-87-0)				
рН	6.3 (1 %)			
Sodium dodecylbenzenesulfonate (25155	-30-0)			
рН	7 – 10.5 (0.1 %, 25 °C, EPA OPPTS 830.7000: pH)			
Serious eye damage/irritation	: Assumed to cause serious eye damage pH: 13			
Nonylphenol Ethoxylate (127087-87-0)				
рН	6.3 (1 %)			
Sodium dodecylbenzenesulfonate (25155	-30-0)			
рН	7 – 10.5 (0.1 %, 25 °C, EPA OPPTS 830.7000: pH)			
Respiratory or skin sensitization Germ cell mutagenicity	: Not classified : Not classified			

5/16/2019 (Issue date) EN (English US) 6/12

: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
butyl glycolether (111-76-2)		
Viscosity, kinematic	3.659 mm²/s	
Sodium dodecylbenzenesulfonate (2515	55-30-0)	
Viscosity, kinematic	No data available in the literature	
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.	
Symptoms/effects	: Causes severe skin burns and eye damage.	
Symptoms/effects after eye contact	: Causes serious eye irritation.	

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term

: Not classified

: Not classified

Hazardous to the aquatic environment, long-term

(chronic)

Nonylphenol Ethoxylate (127087-87-0)		
LC50 - Fish [1]	11.6 mg/l (48 h, Oryzias latipes, Static system, Fresh water, Experimental value)	
EC50 - Crustacea [1]	14 mg/l (48 h, Daphnia magna, Static renewal, Fresh water, Experimental value)	
EC50 96h - Algae [1]	12 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)	
Sodium dodecylbenzenesulfonate (25155-30-0	0)	
LC50 - Fish [1]	3.2 – 5.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Daily renewal, Fresh water, Experimental value, Lethal)	
EC50 - Crustacea [1]	6.3 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)	
EC50 72h - Algae [1]	65.4 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)	

12.2. Persistence and degradability

Power Foam Degreaser		
Persistence and degradability	Not established.	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water, Biodegradable in the soil, Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance	
ThOD	2.305 g O ₂ /g substance	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)		
BOD (% of ThOD) 0.31		
Nonylphenol Ethoxylate (127087-87-0)		
Persistence and degradability Not readily biodegradable in water, Biodegradable in water.		
Sodium dodecylbenzenesulfonate (25155-30-0)		
Persistence and degradability Readily biodegradable in water.		

12.3. Bioaccumulative potential

Power Foam Degreaser			
Bioaccumulative potential	Not established.		
butyl glycolether (111-76-2)			
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Nonylphenol Ethoxylate (127087-87-0)			
BCF - Fish [1]	7.6 – 12.4 l/kg (6 week(s), Cyprinus carpio, Static system, Fresh water, Experimental value)		
Partition coefficient n-octanol/water (Log Pow)	5.67 (Practical experience/observation, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Low potential for bioaccumulation (molecular mass >=700 g/mol).		
Sodium dodecylbenzenesulfonate (25155-30-0)			
BCF - Fish [1]	130 l/kg (Equivalent or similar to OECD 305, 3 day(s), Leuciscus idus, Semi-static system, Fresh water, Experimental value)		
Partition coefficient n-octanol/water (Log Pow)	1.96 (Experimental value, Equivalent or similar to OECD 107, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		

12.4. Mobility in soil

butyl glycolether (111-76-2)		
Surface tension	0.027 N/m (25 °C)	
Nonylphenol Ethoxylate (127087-87-0)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.631 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)	
Ecology - soil	No (test)data on mobility of the substance available. Low potential for adsorption in soil.	
Sodium dodecylbenzenesulfonate (25155-30-0)		
Surface tension	29.3 – 31.8 mN/m (25 °C, 0.012 %)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.96 (log Koc, Calculated value)	
Ecology - soil	Low potential for mobility in soil.	

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

5/16/2019 (Issue date) EN (English US) 8/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Avoid release to the environment.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Ecological information : Avoid release to the environment.

SECTION 14 Transport information

14.1. UN number

UN-No. (DOT) : NA1760
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Compounds, cleaning liquid

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

5/16/2019 (Issue date) EN (English US) 9/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Special precautions for user

DOT

UN-No.(DOT) : NA1760

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

: 30 L

TDG

No data available

IMDG

No data available

IATA

No data available

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
butyl glycolether	111-76-2	Present	Active	
Nonylphenol Ethoxylate	127087-87-0	Present	Active	XU

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	CAS-No.	Listing	Commercial status	Flags
Sodium dodecylbenzenesulfonate	25155-30-0	Present	Active	

Sodium dodecylbenzenesulfonate (25155-30-0)

Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 1000 lb

15.2. International regulations

CANADA

Nonylphenol Ethoxylate (127087-87-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. State regulations

No additional information available

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 5/16/2019Other information: None.

Full text of	Full text of hazard classes and H-statements		
H227	Combustible liquid		
H302	Harmful if swallowed		
H311	Toxic in contact with skin		
H314	Causes severe skin burns and eye damage		
H315	Causes skin irritation		
H318	Causes serious eye damage		
H319	Causes serious eye irritation		
H330	Fatal if inhaled		
H331	Toxic if inhaled		

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

5/16/2019 (Issue date) EN (English US) 11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.