

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/10/2018 Supersedes: 10/23/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Product name : All In One Boiler Water Treatment

Product code : 155-8789

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Water treatment

1.4. Supplier's details

American Cleaning Solutions 39-30 Review Avenue Long Island City, NY, 11101 T (718) 392-8080

1.5. Emergency phone number

Emergency number : INFOTRAC: 800-535-5053

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1 H314 Causes severe skin burns and eye damage.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P260 - Do not breathe dusts or mists.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing

protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor

P321 - Specific treatment (see supplemental first aid instruction on this label).
P363 - Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Sodium Hydroxide, conc=50%, aqueous solution	CAS-No.: 1310-73-2	5 – 10	Skin Corr. 1A, H314
tetrasodium ethylene diamine tetracetate	CAS-No.: 64-02-8		Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice
	(show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

: Causes severe skin burns and eye damage.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and : Based on available data, the classification criteria are not met. symptoms

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

Symptoms/effects

5/10/2018 (Issue date) EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public

waters.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

See Heading 8. Exposure controls and personal protection.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of

vapor. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Wash hands and forearms thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces,

sparks, open flame and other ignition sources. No smoking. Keep container closed when not in

use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

5/10/2018 (Issue date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropiate engineering controls

No additional information available

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves/eye protection/face protection protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):





Other information:

Do not eat, drink or smoke during use.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid Color clear Odor mild

Odor threshold No data available

рΗ : 13

Melting point : No data available Freezing point : No data available Boiling point : 212 - 220 °F : ≥ 200 °F Flash point Flammability (solid, gas) : Non flammable. : No data available Vapor pressure Relative vapor density at 20 °C : Same as water

Relative density

Soluble in water. Solubility Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available

Viscosity, kinematic : 1 mm²/s

Explosion limits : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Particle characteristics : No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : corrosive vapors.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

tetrasodium ethylene diamine tetracetate (64-02-8)		
LD50 oral rat	1780 – 2000 mg/kg (Rat, Male / female, Experimental value, Oral)	
ATE US (oral)	1780 mg/kg body weight	
Ckin parragion/irritation :	Coupage severe akin huma	

Skin corrosion/irritation : Causes severe skin burns

pH: 13

Sodium Hydroxide, conc=50%, aqueous solution (1310-73-2)

> 14 (20 °C)

tetrasodium ethylene diamine tetracetate (64-02-8)

pH 11 (1 %)

Serious eye damage/irritation : Assumed to cause serious eye damage

pH: 13

Sodium Hydroxide, conc=50%, aqueous solution (1310-73-2)

pH > 14 (20 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

tetrasodium ethylene diamine tetracetate (64-02-8)		
рН	11 (1 %)	
Respiratory or skin sensitization	Not classified	
Germ cell mutagenicity	Not classified	
Carcinogenicity	Not classified	
Reproductive toxicity	Not classified	
STOT-single exposure	Not classified	
STOT-repeated exposure	Not classified	
Aspiration hazard	Not classified	
All In One Boiler Water Treatment		
Viscosity, kinematic	1 mm²/s	
Sodium Hydroxide, conc=50%, aqueous solu	ution (1310-73-2)	
Viscosity, kinematic	51.803 mm²/s	
tetrasodium ethylene diamine tetracetate (64	1-02-8)	
Viscosity, kinematic	Not applicable (solid)	
Potential Adverse human health effects and symptoms	Based on available data, the classification criteria are not met.	
Symptoms/effects	Causes severe skin burns and eye damage.	

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

tetrasodium ethylene diamine tetracetate (64-02-8)		
LC50 - Fish [1]	121 mg/l (US EPA, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Soft water)	
EC50 - Crustacea [1]	625 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)	
LC50 - Fish [2]	396 mg/l	
ErC50 algae	> 100 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Weight of evidence, Nominal concentration)	

12.2. Persistence and degradability

All In One Boiler Water Treatment		
Persistence and degradability	Not established.	
Sodium Hydroxide, conc=50%, aqueous solution (1310-73-2)		
Persistence and degradability Biodegradability: not applicable.		
tetrasodium ethylene diamine tetracetate (64-02-8)		
Persistence and degradability Not readily biodegradable in water.		
Biochemical oxygen demand (BOD)	< 0.002 g O ₂ /g substance	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

tetrasodium ethylene diamine tetracetate (64-02-8)	
Chemical oxygen demand (COD)	$0.54 - 0.58 \text{ g O}_2/\text{g substance}$

12.3. Bioaccumulative potential

All In One Boiler Water Treatment		
Bioaccumulative potential	Not established.	
Sodium Hydroxide, conc=50%, aqueous solution (1310-73-2)		
ioaccumulative potential Does not contain bioaccumulative component(s).		
tetrasodium ethylene diamine tetracetate (64-02-8)		
BCF - Fish [1]	1.1 – 1.8 (28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	-13.17 (Estimated value, KOWWIN)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

12.4. Mobility in soil

Sodium Hydroxide, conc=50%, aqueous solution (1310-73-2)		
Ecology - soil No (test)data on mobility of the component(s) available.		
tetrasodium ethylene diamine tetracetate (64-02-8)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.495 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Low potential for adsorption in soil.	

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

Other information : Avoid release to the environment.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Ecological information : Avoid release to the environment.

SECTION 14 Transport information

14.1. UN number

UN-No. (DOT) : UN1760
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. Proper Shipping Name (TDG) : Not applicable

5/10/2018 (Issue date) EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : Not applicable

MDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No.(DOT) : UN1760

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Emergency Response Guide (ERG) Number : 154

IMDG

No data available

IATA

No data available

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Sodium Hydroxide, conc=50%, aqueous solution	1310-73-2	Present	Active	
tetrasodium ethylene diamine tetracetate	64-02-8	Present	Active	

Sodium Hydroxide, conc=50%, aqueous solution (1310-73-2)

Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ 1000 lb

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. State regulations

No additional information available

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date : 5/10/2018 Other information : None.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at

normal temperature and pressure with low risk for explosion. Materials may react violently with

water or form peroxides upon exposure to air.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.